

# Lacing Selection Chart

Clipper

Unibar

Alligator

Staple

Bolt Hinged

Rivet Hinged

Bolt Solid Plate

MS

MR

Minimum Pulley Diameter	Belt Thickness																
	Up to .047" or 3/64"	.063" 1/16"	.093" 3/32"	.125" 1/8"	.156" 5/32"	.187" 3/16"	.219" 7/32"	.25" 1/4"	.281" 9/32"	.313" 5/16"	.375" 11/32"	.406" 25/64"	.438" 7/16"	.500" 1/2"	.563" 9/16"	.625" 5/8"	.688" 11/16"
	Up to 1.2mm	1.6mm	2.4mm	3.2mm	4.0mm	4.8mm	5.6mm	6.4mm	7.1mm	7.9mm	9.0mm	10.0mm	11.1mm	12.7mm	14mm	16mm	17mm
15/16" 24mm	25SP																
	25																
	UCM36SL XSP																
	UCM36SL SP																
	25LP																
00																	
1-1/2"; 38mm		1															
2" 51mm	UCM36 XSP																
	30																
	UCM36 SP																
	36 SP																
	1 XSP																
	30P																
	UX-1 SP																
	RS62																
	MR1																
	UCM36																
	36																
	1 SP																
	7																
	UCM36 LP																
	1																
	UX-1																
	UA2																
U2 SP																	
2SP																	
U2																	
2																	
UA3																	
15																	
2-1/2"; 64mm																	

Chart Continues on Reverse Side